

BEST AVAILABLE COPY




Figure 1: Layout of optical bench in Matteson-Cygnus-26 Fourier Transform Spectrophotometer with Labsphere Integrating sphere accessory installed.




Figure 2. Scanning electron microscope pictures of the hemisphere 400-450 nm coating at 200X (Fig. 2a) and 500X (Fig. 2b). The thinner coating used in the NRL sphere is shown at 100X magnification (Fig. 2c) and 200X magnification (Fig. 2d).




Figure 4: Bidirectional reflectance data for Labsphere 400 micro-inch diffuse gold coating. The data shown was measured at an incidence angle of 30 degrees, a wavelength of 10.6 microns, and a variety of angles in different azimuthal planes ranging from the plane of incidence (top curve) to 126 degrees out of the plane of incidence (bottom curve).




Figure 5: Detector optics coupling schemes: a) baffle, b) collimator, c) reflecting cone, and d) Compound Elliptic Concentrator (CEC).




Figure 6: Average absorption vs. cone half angle for Lambertian illumination of a HgCdTe detector at 10 microns. The high Fresnel reflection losses at large angles do not decrease the average absorption significantly due to the projected area term in the weighting factor.





Figure 7: Integrating sphere detector optics throughput (normalized by CTC throughput) vs. source radius divided by sphere radius. For a source radius of 0.9, the CTC is over five times more efficient at collecting radiation than the optimized collimator.






Figure 8b1 CIE aperture radius (normalized by sphere radius) versus source size for detector radii ranging from .01 to .05 sphere radii. The curves stop where the aperture and source radii become equal, at that point the CIE length is infinity.

CEC PARAMETERS (in.)
Length: 1.473
Detect. Diam.: 0.600
Aperture Diam.: 1.058
Concentration: 3.11
Sphere Diam: 6.00




Figure 9: Effect of refraction compensation on the CEC length and concentration. The upper CEC was designed for the same source, sphere, and detector radii as the lower, however, no cover window over the detector was assumed. The concentration and length for the upper CEC are 2.98 and 1.399 respectively, or about 4.5% less than the refraction compensated case.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.